Town of Cobourg's Accessibility Audit Checklist

Description

- 1. Not Accessible: Facilities that have made no efforts to become accessible, and/or have significant barriers to physical accessibility for people with disabilities.
- 2. **Somewhat Accessible**: Facilities that meet current building code requirements for access but have not gone beyond minimal requirement. Older facilities that are not required to be up to current code but have made efforts to upgrade to code will be labelled here, as long as entrances, washrooms, and customer areas are reasonably accessible for most people with disabilities.
- 3. **Reasonably Accessible**: Meets all of the requirements. Plus most people with disabilities can access all areas of the facility and use all amenities generally available to the public.
- 4. Considered Fully Accessible: Meets all of the requirements of being "Reasonably Accessible" plus entrances, washrooms, seating, and circulation meet ideal accessibility standards as identified in the check lists and all work areas are fully accessible.
- 5. **Exemplary**: Goes beyond the standards in the check lists by providing a high level of accessibility, comfort, and convenience for people with disabilities. These facilities can be considered "models of accessibility."

Shopping

Drop Off/Pick Up

AREA	Yes	Somewhat	No	Additional Notes
Accessible drop				
off				
Min.				
Dimensions 6m				
x 1.5m (19'8" x				
4'11")				
Close to				
accessible				
entrance				
Sheltered				
Overhead				
clearance				
(actual)				
Accessible				
Transit				

Parking

AREA	Yes	Somewhat	No	Additional Notes
Sufficient				
parking spaces				
(5%)				
Designated				
spaces close to				
entrance				
Proper signage				
Min. 3.7 m (12')				
wide (or actual				
measure)				
Overhead				
clearance				
(measure)				

Entrances

AREA	Yes	Somewhat	No	Additional Notes
Wheelchair				
accessible				
Threshold max				
13mm (1/2")				
high				
Automatic				
opener				
Exterior doors				
max 3.87 kg				
(38N) force				
Call button for				
assistance				
If ramp, slope				
max 1/12 width				
min 914.4 mm				
(3')				
If ramp longer				
than 1.83 m (6'),				
railings				

AREA	Yes	Somewhat	No	Additional Notes
1.52m (5')				
landing for				
every 9.14m				
(30') ramp, top,				
bottom, and				
switchback				
If steps, marked				
with				
texture/colour				
If steps,				
handrail				
Door min				
opening 914				
mm (36")				
Door handle				
height 1219.2				
mm (48") or less				
Lever handle				
Large print, high				
contrast signage				
Adequate				
lighting (min				
100 LUX)				

Interiors

AREA	Yes	Somewhat	No	Additional Notes
Corridors at				
least 1.06m				
(3'5") wide				
Corridor free of				
obstructions				
Non-skid				
flooring				
Wheelchair				
accessible				
counters (max				
853 mm; 2'8")				
Barrier-free				
path to service				
counter				

AREA	Yes	Somewhat	No	Additional Notes
Tables with 680				
mm clearance,				
accessible				
Accessible				
directional				
signage				
Doors 2.27 kg				
(5lb) force or				
less				
1.52m (5') circle				
or T space to				
turn chair				
Places to sit and				
rest				
Good lighting				
(min. 100 LUX)				

Elevators

AREA	Yes	Somewhat	No	Additional Notes
Call buttons				
max 1.37 m (4'5")				
Braille or raised buttons				
Doors reopen upon meeting obstacle				
Floor indicator (audible beep and/or voice)				
Sign on both door jams identifying the floor (in raised letters or				
Braille)				

Washrooms

AREA	Yes	Somewhat	No	Additional Notes
Easy access				
(well located)				
Wheelchair				
accessible				
Automatic door				
and/or Lever				
handle				
Min. 914.4mm				
(36") wide door				
opening				
Cubicle min 823				
mm opening				
(27")				
Cubicle min				
1.5m x 1.5m				
(4'11" x 4'11")				
Has Grab Bars				
Grab Bars				
between 762				
and 853 mm				
(2'5" & 2'8")				
Top of toilet				
seat between				
426 to 457 mm				
from floor (1'4"				
and 1'5"(
Min 1.04 m				
(3'5") transfer				
space by toilet				
Min 701 mm				
(2'3") sink				
height				
Level faucet				
handles				
Bottom of				
mirror max 1m				
high (3'3") or				
tilted				
downward				

AREA	Yes	Somewhat	No	Additional Notes
Appropriate				
signage				
Stall door				
operable with				
closed fist				
Unisex				
accessible				
washroom				

AREA	Yes	Somewhat	No	Additional Notes
Have public				
telephones				
Wheelchair				
accessible				
Volume control				
TTY available for				
use				
If more than 4,				
is one TDD				

Restaurants

Drop Off/Pick Up

AREA	Yes	Somewhat	No	Additional Notes
Accessible drop off				
Min. Dimensions 6m x 1.5m (19'8" x 4'11")				
Close to accessible entrance				
Sheltered Overhead				
clearance (actual)				
Accessible Transit				

Parking

AREA	Yes	Somewhat	No	Additional Notes
Sufficient				
parking spaces				
(5%)				
Designated				
spaces close to				
entrance				
Proper signage				
Min. 3.7 m (12')				
wide (or actual				
measure)				
Overhead				
clearance				
(measure)				

Entrances

AREA	Yes	Somewhat	No	Additional Notes
Wheelchair				
accessible				
Threshold max				
13mm (1/2")				
high				
Automatic				
opener				
Exterior doors				
max 3.87 kg				
(38N) force				
Call button for				
assistance				
If ramp, slope				
max 1/12 width				
min 914.4 mm				
(3')				
If ramp longer				
than 1.83 m (6'),				
railings				

AREA	Yes	Somewhat	No	Additional Notes
1.52m (5')				
landing for				
every 9.14m				
(30') ramp, top,				
bottom, and				
switchback				
If steps, marked				
with				
texture/colour				
If steps,				
handrail				
Door min				
opening 914				
mm (36")				
Door handle				
height 1219.2				
mm (48") or less				
Lever handle				
Large print, high				
contrast signage				
Adequate				
lighting (min				
100 LUX)				

Interiors

AREA	Yes	Somewhat	No	Additional Notes
Corridors at				
least 1.06m				
(3'5") wide				
Corridor free of				
obstructions				
Non-skid				
flooring				
Wheelchair				
accessible				
counters (max				
853 mm; 2'8")				
Barrier-free				
path to service				
counter				

AREA	Yes	Somewhat	No	Additional Notes
Tables with 680				
mm clearance,				
accessible				
Accessible				
directional				
signage				
Doors 2.27 kg				
(5lb) force or				
less				
1.52m (5') circle				
or T space to				
turn chair				
Places to sit and				
rest				
Good lighting				
(min. 100 LUX)				

Elevators

Washrooms

AREA	Yes	Somewhat	Νο	Additional Notes
Easy access				
(well located)				
Wheelchair				
accessible				
Automatic door				
and/or Lever				
handle				
Min. 914.4mm				
(36") wide door				
opening				
Cubicle min 823				
mm opening				
(27")				
Cubicle min				
1.5m x 1.5m				
(4'11" x 4'11")				
Has Grab Bars				
Grab Bars				
between 762				
and 853 mm				
(2'5" & 2'8")				
Top of toilet				
seat between				
426 to 457 mm				
from floor (1'4"				
and 1'5"(
Min 1.04 m				
(3'5") transfer				
space by toilet				
Min 701 mm				
(2'3") sink				
height				
Level faucet				
handles				
Bottom of				
mirror max 1m				
high (3'3") or				
tilted				
downward				

AREA	Yes	Somewhat	No	Additional Notes
Appropriate				
signage				
Stall door				
operable with				
closed fist				
Unisex				
accessible				
washroom				

AREA	Yes	Somewhat	No	Additional Notes
Have public				
telephones				
Wheelchair				
accessible				
Volume control				
TTY available for				
use				
If more than 4,				
is one TDD				

Service Counters

AREA	Yes	Somewhat	No	Additional Notes
Wheelchair				
accessible				
counters (max				
860mm/2'8")				
Barrier free				
path to service				
counter				
Food visible to				
patron in				
wheelchair				

Dining Area

AREA	Yes	Somewhat	No	Additional Notes
Menus Available in Braille				

AREA	Yes	Somewhat	No	Additional Notes
Menus Available				
in large font (14				
pt or better)				
Accommodate				
dietary				
restrictions				
Adequate				
lighting				
Adequate room				
to maneuver				
wheelchair				
Non-slip				
flooring				
If carpet, low				
pile				
Tables with				
680mm				
clearance,				
accessible				

Safety

AREA	Yes	Somewhat	Νο	Additional Notes
Alarms with				
flashing lights				
Evacuation plan				
for People with				
Disabilities				
Fire alarm pulls				
max 1.2m (4')				
from floor				
Fire				
extinguishers				
max 1.2m (4')				
from floor				
Audible safety-				
route signaling				
device				
Adequate back-				
up or floor				
lighting for				
emergencies				

Parks

Drop Off/Pick Up

AREA	Yes	Somewhat	No	Additional Notes
Accessible drop				
off				
Min.				
Dimensions 6m				
x 1.5m (19'8" x				
4'11")				
Close to				
accessible				
entrance				
Sheltered				
Overhead				
clearance				
(actual)				
Accessible				
Transit				

Parking

AREA	Yes	Somewhat	No	Additional Notes
Sufficient				
parking spaces				
(5%)				
Designated				
spaces close to				
entrance				
Proper signage				
Min. 3.7 m (12')				
wide (or actual				
measure)				
Overhead				
clearance				
(measure)				

Elevators, if applicable

AREA	Yes	Somewhat	No	Additional Notes
Call buttons				
max 1.37 m				
(4'5")				

AREA	Yes	Somewhat	No	Additional Notes
Braille or raised				
buttons				
Doors reopen				
upon meeting				
obstacle				
Floor indicator				
(audible beep				
and/or voice)				
Sign on both				
door jams				
identifying the				
floor (in raised				
letters or				
Braille)				

Washrooms, if applicable

AREA	Yes	Somewhat	No	Additional Notes
Easy access				
(well located)				
Wheelchair				
accessible				
Automatic door				
and/or Lever				
handle				
Min. 914.4mm				
(36") wide door				
opening				
Cubicle min 823				
mm opening				
(27")				
Cubicle min				
1.5m x 1.5m				
(4'11" x 4'11")				
Has Grab Bars				
Grab Bars				
between 762				
and 853 mm				
(2'5" & 2'8")				

AREA	Yes	Somewhat	No	Additional Notes
Top of toilet				
seat between				
426 to 457 mm				
from floor (1'4"				
and 1'5"(
Min 1.04 m				
(3'5") transfer				
space by toilet				
Min 701 mm				
(2′3″) sink				
height				
Level faucet				
handles				
Bottom of				
mirror max 1m				
high (3'3") or				
tilted				
downward				
Appropriate				
signage				
Stall door				
operable with				
closed fist				
Unisex				
accessible				
washroom				

AREA	Yes	Somewhat	No	Additional Notes
Have public				
telephones				
Wheelchair				
accessible				
Volume control				
TTY available for				
use				
If more than 4,				
is one TDD				

Service Counters, if applicable

AREA	Yes	Somewhat	No	Additional Notes
Wheelchair				
accessible				
counters (max				
860mm/2'8")				
Barrier free				
path to service				
counter				
Food visible to				
patron in				
wheelchair				

Dining Area, if applicable

AREA	Yes	Somewhat	No	Additional Notes
Menus Available				
in Braille				
Menus Available				
in large font (14				
pt or better)				
Accommodate				
dietary				
restrictions				
Adequate				
lighting				
Adequate room				
to maneuver				
wheelchair				
Non-slip				
flooring				
If carpet, low				
pile				
Tables with				
680mm				
clearance,				
accessible				

Picnic Area

AREA	Yes	Somewhat	No	Additional Notes
Barrier free				
path to covered				
areas				
Spaces are				
provided next to				
benches for				
wheelchairs				
Adequate space				
to maneuver for				
wheelchairs				

Play Area

AREA	Yes	Somewhat	No	Additional Notes
Barrier free path to play				
area				
Accessible				
workout				
equipment				
Accessible play				
equipment				
Spaces are				
provided next				
to benches for				
wheelchairs				

Circulation

AREA	Yes	Somewhat	No	Additional Notes
Paved pathways				
If boardwalk,				
hard and slip				
resistant				
Pathways at				
least 1.2m (4')				
wide				
Picnic tables				
accessible				
Accessible path				
to water				

AREA	Yes	Somewhat	No	Additional Notes
Trail surface				
(material)				
Trail surface				
hard, slip-				
resistant				
Trails outlined				
for difficulty and				
maneuverability				
Free of				
obstacles,				
leaves				
Slopes max 1/12				
Places to sit and				
rest				
Well lit (if open				
at night)				

Public Facilities

Drop Off/Pick Up

AREA	Yes	Somewhat	No	Additional Notes
Accessible drop				
off				
Min.				
Dimensions 6m				
x 1.5m (19'8" x				
4'11")				
Close to				
accessible				
entrance				
Sheltered				
Overhead				
clearance				
(actual)				
Accessible				
Transit				

Parking

AREA	Yes	Somewhat	No	Additional Notes
Sufficient				
parking spaces				
(5%)				
Designated				
spaces close to				
entrance				
Proper signage				
Min. 3.7 m (12')				
wide (or actual				
measure)				
Overhead				
clearance				
(measure)				

Elevators

AREA	Yes	Somewhat	No	Additional Notes
Call buttons				
max 1.37 m				
(4'5")				
Braille or raised				
buttons				
Doors reopen				
upon meeting				
obstacle				
Floor indicator				
(audible beep				
and/or voice)				
Sign on both				
door jams				
identifying the				
floor (in raised				
letters or				
Braille)				

Washrooms

AREA	Yes	Somewhat	No	Additional Notes
Easy access (well located)				

AREA	Yes	Somewhat	No	Additional Notes
Wheelchair				
accessible				
Automatic door				
and/or Lever				
handle				
Min. 914.4mm				
(36") wide door				
opening				
Cubicle min 823				
mm opening				
(27")				
Cubicle min				
1.5m x 1.5m				
(4'11" x 4'11")				
Has Grab Bars				
Grab Bars				
between 762				
and 853 mm				
(2'5" & 2'8")				
Top of toilet				
seat between				
426 to 457 mm				
from floor (1'4"				
and 1'5"(
Min 1.04 m				
(3'5") transfer				
space by toilet				
Min 701 mm				
(2'3") sink				
height				
Level faucet				
handles				
Bottom of				
mirror max 1m				
high (3'3") or				
tilted				
downward				
Appropriate				
signage				
JIGHUGC				

AREA	Yes	Somewhat	No	Additional Notes
Stall door				
operable with				
closed fist				
Unisex				
accessible				
washroom				

AREA	Yes	Somewhat	No	Additional Notes
Have public				
telephones				
Wheelchair				
accessible				
Volume control				
TTY available for				
use				
If more than 4,				
is one TDD				

Service Counters

AREA	Yes	Somewhat	No	Additional Notes
Wheelchair				
accessible				
counters (max				
860mm/2'8")				
Barrier free				
path to service				
counter				
Food visible to				
patron in				
wheelchair				

Meeting Rooms/Performance Halls

AREA	Yes	Somewhat	No	Additional Notes
Seating choice				
for people with				
wheelchair				
Induction loop				
for hard of				
hearing				

AREA	Yes	Somewhat	No	Additional Notes
Signage				
indicating loop				
available				
Way finding –				
appropriate				
signage				
Well lit				
Tables with 680				
mm clearance,				
accessible				
Barrier free				
path to table				